# SOLENOIDS

Heavy-duty Hunter 24 VAC or latching solenoids provides dependable operation and long life performance.

# **Key Benefits**

- Compatible with all Hunter irrigation valves
- Engineered with ultra-durable, heavy-duty materials for maximum longevity
- Energy-efficient, low-power design
- Stops water intrusion and protects critical electrical components
- Pre-wired with 46 cm of valvecontrol wire
- Captive plunger offers easy servicing of solenoid
- · Easy installation with no tools required

## **Electrical Specifications**

Manual guarter-turn on/off

#### 606800

control

- Minimum opening/operating voltage: 19 VAC
- Maximum recommended voltage: 28 VAC

- Current at 24 VAC:
  350 mA inrush, 190 mA holding, 60 Hz
  370 mA inrush, 210 mA holding, 50 Hz
  Maximum operating pressure: 15.17 bar; 1517 kPa
- Wire leads: 45 cm of 0.8 mm<sup>2</sup> UL-approved wire

#### 458200

- Minimum opening/operating voltage: 6 VDC Maximum recommended voltage: 9 VDC
- Coil resistance: 4.8 ohms nominal
- Maximum operating pressure: 13.79 bar; 1379 kPa
- Wire leads: 45 cm of 0.8 mm<sup>2</sup> Black and Red UL-approved wire

### Type: Accessory



**AC Solenoid** Height: 7 cm Width: 2.5 cm Depth: 2.5 cm



**DC-Latching Solenoid** Height: 7 cm Width: 2.5 cm Depth: 2.5 cm



Model	Description
	AC Solenoid for all Hunter irrigation valves
606800	*All PGV, ICV, and IBV valves come factory-installed with AC solenoid #606800. Use for replacement or retrofits.
458200	DC-latching solenoid for all Hunter irrigation valves

<b>User-Installed</b>	Options

Model	Description
NODE	
NODE-200	2-station controller (DC-Latching Solenoid ordered separately)
NODE-400	4-station controller (DC latching solenoid ordered separately)
NODE-600	6-station controller (DC latching solenoid ordered separately)
NODE-BT	
NODE-BT-200	2-station Bluetooth battery controller
NODE-BT-400	4-station Bluetooth battery controller
XC Hybrid	
XCH-600	6-Station indoor/outdoor controller
XCH-1200	12-Station indoor/outdoor controller
XCH-600-SS	6-Station outdoor controller, stainless steel
XCH-1200-SS	12-Station outdoor controller, stainless steel
XCH-600-SSP	6-Station outdoor controller, stainless steel, solar
XCH-1200-SSP	12-Station outdoor controller, stainless steel, solar

ACCESSORIES